



# LT2 2700K

October 2023  
1/1

## Specifications

Product Codes	2700KN: natural gas / 2700KP: propane
Product type	Direct Vent, Zero Clearance
Input (BTU)	Natural gas: 39,000 / 22,000      Propane: 39,000 / 20,000
Vent Outlet	4 x 6-5/8" co-axial. Top or Rear outlet.
Venting System	Co-axial 4 x 6-5/8", Co-Linear 3x4.
Gas Convertible	Yes
Valve	GV60
Control	Valor10 remote control; Remote Battery & Wall Switch Kit included
Batteries	Fireplace: 4xAA in Remote Battery & Wall Switch Kit; 3xAAA in Remote control handset
Electrical	Included, via V-module to operate remote control receiver, lighting, and (optional) wifi
Lighting	Yes, requires 2x G6.35 35W halogen bulbs (included)
Wifi	<sup>1</sup> Optional. Operated by Valor10 application on smartphone.
Fan (Blower)	No
HeatShift	<b>Mandatory.</b> 5" outlets at fireplace. Uses LDK1, 3, 4, 7, and 9 kits.
Liners	Fluted black, Plain black, Reflective glass, Charcoal brick
Fuel Beds	Logs: Driftwood, Splitwood, Birch, Murano Glass, or Rock and Shale
Fronts / Trims	Clean Install Kit or Linear 1" Finishing Trim
Outdoor Installation	Yes, with no electrical power connection. Requires GV60CKO Conversion kit
Comments	<sup>1</sup> Optional Wifi requires V-module and electrical power